

Product information

M12 Receptacle connector, front mounting, with stranded wire - RSFM 4/0,5 M

Industrial Connecting Solutions:Circular Connectors:M8 - M12 Connectors:M12 Connectors:M12 Circular connector acc. to IEC 61076-2-101:M12 Receptacle Connectors:M12 Receptacle connector, front mounting, with stranded wire

<https://e-catalog.beldensolutions.com:443/link/57078-24228-256281-256292-256304-58429-58480-76078/en/RSG-04-xM-16/ulistate>

Name M12 Receptacle connector, front mounting, with stranded wire



Receptacle connector, for front mounting, M12 male connector, assembled stranded wire, solder contacts potted with epoxy, 4 poles, A coding, chassis side thread M16 x 1.5 (panel nut RSKFM 16).

Delivery informations

Availability available

Product description

Type RSFM 4/0,5 M

Order No. 26144

Description Receptacle connector, for front mounting, M12 male connector, assembled stranded wire, solder contacts potted with epoxy, 4 poles, A coding, chassis side thread M16 x 1.5 (panel nut RSKFM 16).

Number of contacts 4

Color of housing silver

Product characteristics Oil resistance

Classification

Belden brand Lumberg-Automation

Eclass-ID 27260702

Mechanical data

Type of plug-in contact Male connector

Design of housing straight

Thread M12

Design of electrical connection stranded wire

Coding of the M12 round plug connector A

LED display present **✘**

Environmental conditions

Environmental temperature -25 °C ... 80 °C

Degree of protection (IP), mounted IP67

Pollution degree 3

Materials

Housing material / Molded body CuZn, nickel-plated

Contact material CuZn

Contact material - Surface refinement pre-nickeled and 0.8 microns gold-plated

Sealing material FKM

Electrical data

Contact resistance $\leq 5 \text{ m}\Omega$

Rated current I_n 4 A at 40°C, UL and notice derating

Nominal voltage 240 V

Rated voltage 250 V

Test voltage 2.0 kV eff./60 s

Insulation resistance $> 1 \text{ G}\Omega$

Approvals

Approvals UL

Belden Deutschland GmbH

Im Gewerbepark 2
58579 Schalksmühle
Germany
Phone: +49 7127/14-1806
E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.