


## Product information

### RSMV-RKMVV/LED - RSMV 3-RKMVV/LED A 3-224/2 M

Industrial Connecting Solutions:Cables and Adapters:Connecting and Data Cables:M8, M12, M23, Valve Connectors - Connecting Cables:M8 Male Connector on M8 Female Connector:RSMV-RKMVV/LED  
[https://e-catalog.beldensolutions.com:443/link/57078-24228-256254-248344-248345-248348-250792/en/RSMV3\\_RKMVV.L3\\_224\\_0200/uistate](https://e-catalog.beldensolutions.com:443/link/57078-24228-256254-248344-248345-248348-250792/en/RSMV3_RKMVV.L3_224_0200/uistate)


Name	RSMV-RKMVV/LED
	
	Cordset, double ended, for sensors and actuators, M8 male connector with self-locking threaded joint, straight, 3-poles, M8 female connector with snap-in joint, angled, 3-poles, LED operation and function indicator (pnp), with self-locking threaded joint, 2 meters.
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Type	RSMV 3-RKMVV/LED A 3-224/2 M
Order No.	43680
Description	Cordset, double ended, for sensors and actuators, M8 male connector with self-locking threaded joint, straight, 3-poles, M8 female connector with snap-in joint, angled, 3-poles, LED operation and function indicator (pnp), with self-locking threaded joint, 2 meters.
Note	The application of these products in harsh environments should always be checked before use.
Number of contacts	3
Color of housing	black translucent
Color of Housing, side 2	black translucent
Product characteristics	Vibration resistance, Oil resistance, Drag chains suitable
<b>Classification</b>	
Belden brand	Lumberg-Automation
<b>Mechanical data</b>	
Type of plug-in contact	Male connector
Type of plug-in contact, side 2	Female connector
Design of housing	straight
Design of housing, side 2	angled
Thread	M8
Thread, side 2	M8
Design of electrical connection	connector M8
Design of electrical connection, side 2	connector M8
LED display present	✓
<b>Environmental conditions</b>	
Environmental temperature	-40 °C ... 90 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
<b>Materials</b>	
Housing material / Molded body	TPU
Housing material / Molded body, side 2	TPU
Contact bearer material	PA/TPU
Contact bearer material, side 2	PA/TPU
Contact material	CuZn
Contact material - Surface refinement	pre-nickel and 0.3 microns gold-plated
Contact material, side 2	CuZn
Contact material - Surface refinement, side 2	pre-nickel and 0.3 microns gold-plated
Knurled screw / nut material	CuZn, nickel-plated
Sealing material	FKM (Female)
<b>Electrical data</b>	
Rated current In	4 A at 40°C
Nominal voltage	10 - 30 V DC

Industrial Connecting Solutions:Cables and Adapters:Connecting and Data Cables:M8, M12, M23, Valve Connectors - Connecting Cables:M8 Male Connector on M8 Female Connector:RSMV-RKMVV/LED  
[https://e-catalog.beldensolutions.com:443/link/57078-24228-256254-248344-248345-248348-250792/en/RSMV3\\_RKMVV3\\_224\\_0200/ui:state](https://e-catalog.beldensolutions.com:443/link/57078-24228-256254-248344-248345-248348-250792/en/RSMV3_RKMVV3_224_0200/ui:state)

Rated voltage	32 V
Test voltage	1.5 kV eff./60 s
Insulation resistance	> 1 GΩ
<b>Approvals</b>	
Approvals	UL
RoHS 2002/95/EG compliant	yes
<b>Cable</b>	
Cable length	2 m
Cable number	224
Cable description	Cable for sensors and actuators
Color of jacket	black
Material of outer jacket	PUR
Without halogens as in EN 50267-2-3	✓
shielded	✗
welding spark proof	✗
Outer diameter of the cable	4.3 mm
Number of conductors	3
Cable design	3 x 0.34 mm <sup>2</sup>
Conductor design	43 x ø 0.10 mm
Flame resistant according to standard	yes

**Picture**

Drawing



**Belden Deutschland GmbH**

Im Gewerbepark 2  
58579 Schalksmühle  
Germany  
Phone: +49 7127/14-1806  
E-Mail: [icos-sales@belden.com](mailto:icos-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.