


Product information

M12 Receptacle connector, front mounting with stranded wire, bus connectors - 0976 PFC 151

Industrial Connecting Solutions:Circular Connectors:M8 - M12 Connectors:M12 Connectors:M12 Circular connector acc. to IEC 61076-2-101:M12 Receptacle Connectors:M12 Receptacle connector, front mounting with stranded wire, bus connectors

<https://www.e-catalog.beldensolutions.com:443/link/57078-24228-256281-256292-256304-58429-58480-76230/en/RKG-05-CB/uistate>

Name		M12 Receptacle connector, front mounting with stranded wire, bus connectors
		
		Receptacle connector, for front mounting, assembled stranded wire (0.5 m), solder contacts potted with epoxy, with adjustable nut, 5 poles, B coding:especially suitable for Profibus, M12 female connector, chassis side thread M16 x 1.5
Delivery informations		
Availability	available	
Product description		
Type	0976 PFC 151	
Order No.	18317	
Description	Receptacle connector, for front mounting, assembled stranded wire (0.5 m), solder contacts potted with epoxy, with adjustable nut, 5 poles, B coding:especially suitable for Profibus, M12 female connector, chassis side thread M16 x 1.5	
Number of contacts	5	
Color of housing	silver	
Product characteristics	Oil resistance	
Classification		
Belden brand	Lumberg-Automation	
Eclass-ID	27260702	
Mechanical data		
Type of plug-in contact	Female connector	
Design of housing	straight	
Thread	M12	
Design of electrical connection	stranded wire	
Coding of the M12 round plug connector	B	
LED display present	✘	
Environmental conditions		
Environmental temperature	-25 °C ... 80 °C	
Degree of protection (IP), mounted	IP67	
Pollution degree	3	
Materials		
Housing material / Molded body	CuZn, nickel-plated	
Contact bearer material	TPU	
Contact material	CuZn	
Contact material - Surface refinement	pre-nickel and 0.8 microns gold-plated	
Knurled screw / nut material	CuZn, nickel-plated	
Sealing material	FKM	
Electrical data		
Contact resistance	≤ 5 mΩ	
Rated current In	4 A at 40°C, UL and notice derating	
Nominal voltage	60 V	
Test voltage	1.5 kV eff./60 s	
Insulation resistance	> 1 GΩ	
Approvals		
Approvals	UL	

Belden Deutschland GmbH

Im Gewerbepark 2
58579 Schalksmühle
Germany
Phone: +49 7127/14-1806
E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.