

## Han 10B-HMC-gs-R-M25



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 19 30 210 1541                                                                        |
| Specification      | Han 10B-HMC-gs-R-M25                                                                  |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19302101541">https://b2b.harting.com/19302101541</a> |

### Identification

|                          |                      |
|--------------------------|----------------------|
| Category                 | Hoods/Housings       |
| Series of hoods/housings | Han <sup>®</sup> HMC |
| Type of hood/housing     | Hood                 |
| Type                     | Low construction     |

### Version

|                      |                                                   |
|----------------------|---------------------------------------------------|
| Locking type         | Single locking lever                              |
| Size                 | 10 B                                              |
| Version              | Side entry                                        |
| Cable entry          | 1x M25                                            |
| Field of application | Special hoods and housings for high mating cycles |

### Technical characteristics

|                                         |                 |
|-----------------------------------------|-----------------|
| Limiting temperature                    | -40 ... +125 °C |
| Mating cycles with other HMC components | ≥10,000         |
| Degree of protection acc. to IEC 60529  | IP65            |
| Type rating acc. to UL 50 / UL 50E      | 4               |
|                                         | 4X              |
|                                         | 12              |

### Material properties

|                         |                      |
|-------------------------|----------------------|
| Material (hood/housing) | Aluminium die-cast   |
| Surface (hood/housing)  | Powder-coated        |
| Colour (hood/housing)   | RAL 7037 (dust grey) |



Pushing Performance

## Material properties

|                             |           |
|-----------------------------|-----------|
| RoHS                        | compliant |
| ELV status                  | compliant |
| China RoHS                  | e         |
| REACH Annex XVII substances | No        |
| REACH ANNEX XIV substances  | No        |
| REACH SVHC substances       | No        |

## Specifications and approvals

|           |        |
|-----------|--------|
| Approvals | DNV GL |
|-----------|--------|

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Net weight                     | 150.7 g                                  |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |