


Product information

ASB 8 5-4-331/... M - ASB 8 5-4-331/5 M

Industrial Connecting Solutions:I/O Modules:Passive distributors:M12 Passive Distributors:fixed control cable:without LED:1 signal/socket (3+PE):ASB 8 5-4-331/... M

https://www.e-catalog.beldensolutions.com:443/link/57078-24228-255441-199791-200292-204934-204941-204950-204964/en/ASB_08_5_4_331_05/ui/state

Name	ASB 8 5-4-331/... M
	
	Actuator/sensor distribution box, 8-port version, combined FIXCON-/M12 socket, 4-pole, 1 signal per socket, earth connection, fixed connection cable, PUR jacket, halogen-free, black, 5 meter.
Delivery informations	
Availability	available
Product description	
Type	ASB 8 5-4-331/5 M
Order No.	60585
Description	Actuator/sensor distribution box, 8-port version, combined FIXCON-/M12 socket, 4-pole, 1 signal per socket, earth connection, fixed connection cable, PUR jacket, halogen-free, black, 5 meter.
Number of contacts	4 (M12)
Version	8 ports
Color of housing	orange
Product characteristics	Vibration resistance, Oil resistance, Drag chains suitable
Classification	
Belden brand	Lumberg-Automation
Mechanical data	
Thread	M12
LED display present	✘
Environmental conditions	
Environmental temperature	-15 °C ... 80 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
Materials	
Housing material / Molded body	TPU, self-extinguishing
Contact bearer material	PA-GF, self-extinguishing
Contact material	CuZn (M12)
Contact material - Surface refinement	pre-nickel and 0.8 microns gold-plated
Knurled screw / nut material	CuZn, nickel-plated
Sealing material	FKM
Electrical data	
Contact resistance	≤ 5 mΩ
Rated current In	4 A per socket / 12 A max. at 40°C
Nominal voltage	60 V
Rated voltage	63 V
Test voltage	1.0 kV eff./60 s
Insulation resistance	> 1 GΩ
Approvals	
Approvals	cURus
Cable	
Cable length	5 m
Cable number	331
Cable description	Control cable
Color of jacket	black
Material of outer jacket	PUR


Industrial Connecting Solutions:I/O Modules:Passive distributors:M12 Passive Distributors:fixed control cable:without LED:1 signal/socket (3+PE):ASB 8 5-4-331/... M

https://www.e-catalog.beldensolutions.com:443/link/57078-24228-255441-199791-200292-204934-204941-204950-204964/en/ASB_08_5_4_331_05/ui:state

Outer diameter of the cable	8.0 mm
Number of conductors	11
Cable design	8 x 0.34 mm ² + 3 x 0.75 mm ²
Flame resistant according to standard	IEC 60332-2, CSA FT-2
Scope of delivery and accessories	
Scope of delivery	ZVK: 2 dust covers for unused sockets ZBS: 10 attachable labels

Picture

Drawing



Belden Deutschland GmbH
 Im Gewerbepark 2
 58579 Schalksmühle
 Germany
 Phone: +49 7127/14-1806
 E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.